



# D<sup>o</sup>

## HIGH TEMP

High-temperature dosing pump

Food &  
hygiene



**Dosatron** is one of the main actor in the processes **detergence** and **disincfection** in the Food & Hygiene Industry

**DOSATRON APP**  
Your daily assistant



[www.dosatron.com](http://www.dosatron.com)



©DOSATRON INTERNATIONAL S.A.S 2023 - DOCFAPHEN-02/23 - Photo credit : Adobe Stock



**DOSATRON<sup>®</sup>**  
*Because life is powered by water<sup>®</sup>*

This document does not form a contractual engagement and is for information purposes only. DOSATRON INTERNATIONAL reserves the right to modify its devices at any time.



CIP (clean in place) with simple installation:  
D3 range can be used

	D3RE3000	D3RE2	D3RE5	D3RE10	D3RE25IE
Operating flow min./max.	10l/h mini (option T° 100 l/h mini) - 3m³/h maxi [1/3 (option T° 3.5) US Pint/min (min.) - 14 US GPM (max.)]				10l/h mini - 2m³/h maxi [1/3 US Pint/min (min.) - 9 US GPM (max.)]
Maximum operating temperature	<b>40°C / 104°F</b>				
Operating water pressure min./max.	0,3 - 6 bar [4.3 - 85 PSI]		0,5 - 6 bar [7 - 85 PSI]		0,5 - 4 bar [7 - 57 PSI]
Dosing % min./max.	0,03% to 0,3% 1:3000 - 1:333	0,2% to 2% 1:500 - 1:50	0,5% to 5% 1:200 - 1:20	1% to 10% 1:100 - 1:10	5% to 25% 1:20 - 1:4
Version serial option					
Connection	3/4" Male BSP/NPT - Ø20x27 mm				
	Please refer to our documentation for technical performances for high temperature dosing models (70°C max.); D3TRE3000, D3TRE5, D3TRE10				



Centralised cleaning system  
with system connected to satellites:  
D8 range can be used

	D8RE3000	D8RE2	D8RE5
Operating flow min./max.	500l/h mini - 8m³/h maxi [2.2 US Pint/min (min.) - 40 US GPM (max.)]		
Maximum operating temperature	<b>40°C / 104°F</b>		
Operating water pressure min./max.	0,15 - 8 bar [2.2 - 116 PSI]		
Dosing % min./max.	0,03% to 0,125% 1:3000 - 1:800	0,2% to 2% 1:500 - 1:50	1% to 5% 1:100 - 1:20
Version serial option			
Connection	1 1/2" Male BSP/NPT - Ø40x49 mm		



Centralised cleaning system



Standard installation



Entry way sanitation



Entry way sanitation:  
D25 range can be used

	D25RE2	D25RE5
Operating flow min./max.	10l/h mini - 2.5m³/h maxi [1/3 US Pint/min (min.) - 11 US GPM (max.)]	
Maximum operating temperature	<b>40°C / 104°F</b>	
Operating water pressure min./max.	0.3 - 6 bar [4.3 - 85 PSI]	
Dosing % min./max.	0.2% to 2% 1:500 - 1:50	1% to 5% 1:100 - 1:20
Version serial option		
Connection	3/4" Male BSP/NPT - Ø20x27 mm	



Dosing system for entry way sanitation