



# DOSATRON®

WATER POWERED DOSING TECHNOLOGY

## 14 GPM: D14MZ10

### PRODUCT DESCRIPTION

The versatile Dosatron **D14MZ10-14 GPM** is easy to install with the Industrial Plumbing Kit (IPK34-14GPM) and is easy to maintain (see details on second page).

### PRODUCT SPECIFICATIONS

Dilution Range:	1:100 to 1:10 (1% to 10%)
Water Flow Range:	0.05 to 14 GPM
Operating Pressure Range:	7 to 85 PSI
Available Housing Materials:	<ul style="list-style-type: none"> <li>• Polypropylene (Standard Blue)</li> <li>• PVDF</li> </ul>
Other Options:	Viscous
Dimensions:	19 1/18" x 6 5/16"
Weight:	6 lbs
Connection Size:	3/4" NPT
Maximum Temperature:	104° F
Included Accessories:	6' clear suction tube, strainer, weight, mounting bracket and quick start guide
Recommended Accessories:	Pressure regulator, 200 mesh filter, check valve



### MAINTENANCE KITS

Mini-Maintenance Kit (Part #: **PJDI122MINI-H**) - For regular maintenance

Injection Seal Kit (Part #: **PJDI122**) - For yearly maintenance

Injection Seal Kit for Viscous (Part #: **PJDI122V**) - For yearly maintenance

Rebuild Kit (Part #: **MKD14MZ10**) - Extends the life of your Dosatron

**Call 800-523-8499 to order the Dosatron for your specific application**




# DOSATRON®

WATER POWERED DOSING TECHNOLOGY

## 14 GPM: D14MZ10

### Recommended Installation for Industrial Applications

#### IPK34 - 14 GPM Industrial Plumbing Kit



- 3/4" polypropylene single union ball valve
- 1/2" stainless steel ball valve
- 3/4" poly 200 mesh tee filter
- 3/4" brass pressure regulator w/gauge
- 3/4" 14 GPM flow restrictor
- 3/4" polypropylene check valve
- 3/4" union schedule 80 PVC
- 3/4" x 2" polypropylene fittings
- 1/2" x 2" polypropylene fittings
- 1/2" x 1/2" barb fitting
- 3/4" male to 1/2" female reducer bushing
- 3/4" Tee
- 3/4" street elbows
- Roll of thread tape
- Instruction card
- Zip tie

Dosatron International  
2090 Sunnydale Blvd. • Clearwater, FL, USA  
800-523-8499 • [www.dosatronusa.com](http://www.dosatronusa.com)