

An Ingersoll Rand Business

## 14 GPM: D14MZ2

## **PRODUCT DESCRIPTION**

The versatile Dosatron **D14MZ2-14 GPM** is used in industries from irrigation to metal processing. Is easy to install on a boom, cart, or plumbed into a system. It can also be installed with the Industrial Plumbing Kit (IPK34-14GPM) and is easy to maintain (see details on second page).

## **PRODUCT SPECIFICATIONS**

Dilution Range:	1:500 to 1:50 (0.2% to 2%)
Water Flow Range:	0.05 to 14 GPM
<b>Operating Pressure Range:</b>	4.3 to 85 PSI
Available Housing Materials:	<ul><li>Polypropylene (Standard Blue)</li><li>PVDF (White)</li></ul>
Dimensions:	19 1/18" x 6 5/16"
Weight:	6 lbs
Connection Size:	3/4" NPT
Maximum Temperature:	104 <sup>0</sup> F
Included Accessories:	6' clear suction tube, strainer, weight, mounting bracket and quick start guide
Recommended Accessories:	IPK34, Bypass - part #: MPDI196



### MAINTENANCE KITS

Mini-Maintenance Kit (Part #: PJDI116MINI-H) - For regular maintenance Injection Seal Kit (Part #: PJDI116) - For yearly maintenance Rebuild Kit (Part #: MKD14MZ2) - Extends the life of your Dosatron



An Ingersoll Rand Business

# 14 GPM: D14MZ2

#### **Recommended Installation for Industrial Applications**

IPK34 - 14 GPM Industrial Plumbing Kit



3/4" polypropylene single union ball valve 1/2" stainless steel ball valve 3/4" poly 200 mesh tee filter 3/4" brass pressure regulator w/gauge 3/4" 14 GPM flow restrictor 3/4" polypropylene check valve 3/4" union schedule 80 PVC 3/4" x 2" polypropylene fittings 1/2" x 2" polypropylene fittings 1/2" x 1/2" barb fitting 3/4" male to 1/2" female reducer bushing 3/4" Tee 3/4" street elbows Roll of thread tape Instruction card Zip tie

Dosatron International 2090 Sunnydale Blvd. • Clearwater, FL, USA 800-523-8499 • www.dosatron.com