

An Ingersoll Rand Business

9 GPM: D14MZ520

PRODUCT DESCRIPTION

The water-powered Dosatron **D14MZ520-9 GPM** side inject, is easy to install with the Industrial Plumbing Kit (IPK34-9GPM) and is easy to maintain. Industrial applications include metal processing along with food safety and sanitation.



Dilution Range:	1:20 to 1:5 (5% to 20%)
Water Flow Range:	0.05 to 9 GPM
Operating Pressure Range:	7 to 57 PSI
Available Housing Materials:	Polypropylene (Standard Blue)PVDF (White)
Dimensions:	26 1/8" x 10 1/4"
Weight:	8.8 lbs
Connection Size:	3/4" NPT
Maximum Temperature:	104 ^o F
Included Accessories:	6' clear suction tube, strainer, weight, mounting bracket and quick start guide
Recommended Accessories:	IPK34, Bypass - part #: MPDI196



MAINTENANCE KITS

Injection Seal Kit (Part #: PJDI135 - For serial # up to 13400000) - For yearly maintenance

Injection Seal Kit (Part #: PJDI167 - For serial # 13400000-16290362) - For yearly maintenance

Injection Seal Kit (Part #: PJDI199 - For serial # over 16290363) - For yearly maintenance

Call 800-523-8499 to order the Dosatron for your specific application



9 GPM: D14MZ520

Recommended Installation for Industrial Applications

IPK34 - 9 GPM Industrial Plumbing Kit



3/4" polypropylene single union ball valve

1/2" stainless steel ball valve

3/4" poly 200 mesh tee filter

3/4" brass pressure regulator w/gauge

3/4" 9 GPM flow restrictor

3/4" polypropylene check valve

3/4" union schedule 80 PVC

3/4" x 2" polypropylene fittings

1/2" x 2" polypropylene fittings

1/2" x 1/2" barb fitting

3/4" male to 1/2" female reducer bushing

3/4" Tee

3/4" street elbows

Roll of thread tape

Instruction card

Zip tie

Dosatron International 2090 Sunnydale Blvd. • Clearwater, FL, USA 800-523-8499 • www.dosatron.com