

An Ingersoll Rand Business

14 GPM: D14MZ10

PRODUCT DESCRIPTION

The versatile Dosatron **D14MZ10-14 GPM** is easy to install with the Industrial Plumbing Kit (IPK34-14GPM) and is easy to maintain (see details on second page).

PRODUCT SPECIFICATIONS

Dilution Range:	1:100 to 1:10 (1% to 10%)
Water Flow Range:	0.05 to 14 GPM
Operating Pressure Range:	7 to 85 PSI
Available Housing Materials:	Polypropylene (Standard Blue)PVDF
Other Options:	Viscous
Dimensions:	19 1/18" x 6 5/16"
Weight:	6 lbs
Connection Size:	3/4" NPT
Maximum Temperature:	104 ^o F
Included Accessories:	6' clear suction tube, strainer, weight, mounting bracket and quick start guide
Recommended Accessories:	Pressure regulator, 200 mesh filter, check valve



MAINTENANCE KITS

Mini-Maintenance Kit (Part #: PJDI122MINI-H) - For regular maintenance

Injection Seal Kit (Part #: PJDI122) - For yearly maintenance

Injection Seal Kit for Viscous (Part #: PJDI122V) - For yearly maintenance

Rebuild Kit (Part #: MKD14MZ10) - Extends the life of your Dosatron

Call 800-523-8499 to order the Dosatron for your specific application



14 GPM: D14MZ10

Recommended Installation for Industrial Applications

IPK34 - 14 GPM Industrial Plumbing Kit



3/4" polypropylene single union ball valve

1/2" stainless steel ball valve

3/4" poly 200 mesh tee filter

3/4" brass pressure regulator w/gauge

3/4" 14 GPM flow restrictor

3/4" polypropylene check valve

3/4" union schedule 80 PVC

3/4" x 2" polypropylene fittings

1/2" x 2" polypropylene fittings

1/2" x 1/2" barb fitting

3/4" male to 1/2" female reducer bushing

3/4" Tee

3/4" street elbows

Roll of thread tape

Instruction card

Zip tie

Dosatron International 2090 Sunnydale Blvd. • Clearwater, FL, USA 800-523-8499 • www.dosatron.com